## 490A-DL Shock Absorbing Web Lanyard

## **Product Description:**

This dual-leg web lanyard with pack style shock absorber limits fall arrest forces to 900 lbs. when tested to OSHA and ANSI standards.

## **Product Features:**

- 1 3/4" polyester webbing with shock pack
- Dual-leg, 100% tie-off
- Standard length 6', additional lengths available
- · Additional snaphook options available

MATERIAL SPECIFICATIONS		
Hardware	Z74 snap hook, 3/4" gate opening, plated alloy steel	
	100% proof loaded to 3,600 lbs min. tensile 5,000 lbs	
	100% gate loaded to 3,600 lbs	
Webbing	1-3/4" polyester, minimum tensile strength of 6,000 lbs	
	1-3/4" Tear-away	
Thread	Black polyester nubond	

PEFORMANCE SPECIFICATIONS			
ANSI User Capacity	130-310 lbs. Max		
OSHA User Capacity	400 lbs. Max		
Arrest Force	900 lbs		
Lanyard Class	6' Free Fall		

RELEVANT STANDARDS		
ANSI	ANSI Z359.13-2013	
OSHA	Meets or exceeds all OSHA requirements	

## SIZES/LENGTHS

Standard length 6' additional sizes may be available Item weight 3.20 Lbs.

