



PRODUCT SPECIFICATIONS

490ADLDD Shock Absorbing Web Lanyard

Product Description:

This dual-leg web lanyard with pack style shock absorber limits fall arrest forces to 900 lbs. when tested to OSHA and ANSI standards.

Product Features:

- 1-3/4" webbing with shock pack
- Dual-leg, 100% tie-off
- (2) Sliding D-rings on lanyard legs for tie-back
- Standard length 6', additional lengths available
- Additional snaphook options available



MATERIAL SPECIFICATIONS

Hardware	Z74 snap hooks, 3/4" gate opening, plated alloy steel
	100% proof loaded to 3,600 lbs min. tensile 5,000 lbs
	min tensile strength 5,000 lbs
	72F D-ring adjusters: zinc plated steel
	Min tensile strength 5,000 lbs
Webbing	1-3/4" Polyester, minimum tensile strength of 6,000 lbs
	1-3/4" Tear-away
Thread	Black polyester nubond

PERFORMANCE SPECIFICATIONS

ANSI User Capacity	130-310 lbs. Max
OSHA User Capacity	400 lbs. Max
Arrest Force	900 lbs
Lanyard Class	6' Free Fall

RELEVANT STANDARDS

ANSI	ANSI Z359.1-2007
OSHA	Meets or exceeds all OSHA requirements

SIZES/LENGTHS

Standard length 6' additional sizes may be available
Item weight 3.20 Lbs.