



# PRODUCT SPECIFICATIONS

1772

## Product Description:

The 1772 Reusable Concrete Hole Anchor is a compact, high-strength anchorage connector designed for use in concrete substrates as part of a personal fall protection system. Engineered for easy installation and removal, the 1772 provides a secure, reusable anchoring solution for professionals working at height in construction, utilities, and industrial applications.

## Product Features:

- 3/4" portable/reusable concrete hole anchor
- Used overhead and on concrete walls
- Portable and reusable
- Anchor rotates 360° and pivots 180° to avoid tangles



## MATERIAL SPECIFICATIONS

<b>Hardware</b>	D-ring: plated steel & stainless components. Proof loaded 3,600 lbs.
	Chocks and wedge: Stainless steel
	Springs plated steel

## PERFORMANCE SPECIFICATIONS

<b>ANSI User Capacity</b>	130-310 lbs.
<b>OSHA User Capacity</b>	400 lbs.
<b>Anchor Rating</b>	5,000 lbs.

## RELEVANT STANDARDS

<b>ANSI</b>	Z359.18-2017 Type A
<b>OSHA</b>	1926.502 & 1910.140

## Notes

Requires 3/4" concrete hole, min depth 3.5"  
Concrete must have 3,000 psi compressive strength