



PRODUCT SPECIFICATIONS

XR-11S Self Retracting Lifeline

Product Description:

The Outlaw Series SRL's provide durability and confidence expected by professionals. All units feature lightweight housings, and short fall arrest capabilities

Product Features:

- 11' steel cable
- Class "1" SRL
- 3/4" opening swivel snaphook
- 1" opening steel carabiner
- Also available in stainless steel cable or technora synthetic rope

MATERIAL SPECIFICATIONS

Lifeline	11' stainless steel cable 3/16", tensile strength 3,600 lbs
Housing/ Hardware	Thermo-plastic and aluminum
	Drum: aluminum alloy, main shaft: stainless steel
	Ratchet center & brake pawls: brass
	Springs & fasteners: stainless steel, motor spring: carbon steel
Carabiner	#354-4, 1" opening, plated alloy steel 3,600 lb gate, min tensile strength 5,000 lbs
Snaphook	#RL-28, 3/4" opening alloy steel swivel snap hook, impact indicator 3,600 lb gate, Min tensile strength 5,000 lbs

PERFORMANCE SPECIFICATIONS

ANSI User Capacity	130-310 lbs. Max
OSHA User Capacity	400 lbs. Max
Arresting Force	Average arresting force 1,350 lbs, Max 1,800 lbs
Max Arrest Distance	42 inches, max free fall distance 24 inches

RELEVANT STANDARDS

ANSI	ANSI Z359.14-2021 "Class 1" SRL
OSHA	1926.502 & 1910.66

SIZES/LENGTHS

11' length
Item weight 6 lbs

