

XR-11T Self Retracting Lifeline

Product Description:

The Outlaw Series SRL's provide durability and confidence expected by professionals. All units feature lightweight housings, and short fall arrest capabilities

Product Features:

- 11' Technora® synthetic rope SRL
- · Class "1" SRL
- 3/4" opening swivel snaphook
- 1" opening steel carabiner
- · Also available in stainless steel or galvanized cable

| MATERIAL SPECIFICATIONS | | | |
|--------------------------|--|--|--|
| Lifeine Con- stituent | 11' Technora® synthetic rope 3/16", tensile strength 5,600 lbs | | |
| Housing/ Hardware | Thermo-plastic and aluminum | | |
| | Drum: aluminum alloy, main shaft: stainless steel | | |
| | Ratchet center & brake pawls: brass | | |
| | Springs & fasteners: stainless steel, motor spring: carbon steel | | |
| Carabiner | #354-4, 1" opening plated alloy steel 3,600 lb. gate, min tensile strength 5,000 lbs | | |
| Snaphook | #RL-28, 3/4" opening alloy steel swivel snap hook, impact indicator | | |
| | 3,600 lb gate, min tensile strength 5,000 lbs | | |
| | | | |

| PEFORMANCE SPECIFICATIONS | | | | |
|---------------------------|--|--|--|--|
| ANSI User Capacity | 130-310 lbs. Max | | | |
| OSHA User Capacity | 400 lbs. Max | | | |
| Arresting Force | Average arresting force 1,350 lbs, Max 1,800 lbs | | | |
| Max Arrest Distance | 42 inches, max free fall distance 24 inches | | | |

| RELEVANT STANDARDS | | | |
|--------------------|---------------------------------|--|--|
| ANSI | ANSI Z359.14-2021 "Class 1" SRL | | |
| OSHA | 1926.502 & 1910.66 | | |
| | | | |
| | | | |

| SIZES/LENGTHS | | | | |
|---------------------------------|--|--|--|--|
| 11' length Item weight 6 lbs | | | | |

