



PRODUCT SPECIFICATIONS

XR-30S-SSHW Self Retracting Lifeline

Product Description:

The Outlaw Series SRL's provide durability and confidence expected by professionals. With multiple lengths of working capacity and short fall arrest capability, the Outlaw will never let you down.

Product Features:

- 30' stainless steel cable SRL
- Class "2" SRL
- 1" opening stainless steel carabiners
- Also available in galvanized steel cable or Technora® synthetic rope

MATERIAL SPECIFICATIONS

Lifeline Constituent	30' stainless steel cable 3/16", tensile strength 3,600 lbs
Housing/Hardware	Thermo-plastic and aluminum
	Drum: aluminum alloy, main shaft: stainless steel
	Ratchet center & brake pawls: brass
	Springs & fasteners: stainless steel, motor spring: carbon steel
Carabiners	#354-4SS, 1" opening stainless steel, 3,600 lb. gate, min tensile strength 5,000 lbs

PERFORMANCE SPECIFICATIONS

ANSI User Capacity	130-310 lbs. Max
OSHA User Capacity	400 lbs. Max
Arresting Force	Average arresting force 1,350 lbs, Max 1,800 lbs
Max Arrest Distance	42 inches, max free fall distance 24"

RELEVANT STANDARDS

ANSI	ANSI Z359.14-2021 "Class 2" SRL
OSHA	1926.502 & 1910.66

SIZES/LENGTHS

30' length
Item weight 6 lbs

