



PRODUCT SPECIFICATIONS

XR-30S Self Retracting Lifeline

Product Description:

The Outlaw Series SRL's provide durability and confidence expected by professionals. With multiple lengths of working capacity and short fall arrest capability, the Outlaw will never let you down.

Product Features:

- 30' stainless steel cable SRL
- Class "1" SRL
- 3/4" opening swivel snaphook
- 1" opening steel carabiner
- Also available in galvanized steel cable or Technora® synthetic rope

MATERIAL SPECIFICATIONS

| | |
|-----------------------------|---|
| Lifeline Constituent | 30' stainless steel cable 3/16", tensile strength 3,600 lbs |
| Housing/Hardware | Thermo-plastic and aluminum |
| | Drum: aluminum alloy, main shaft: stainless steel |
| | Ratchet center & brake pawls: brass |
| | Springs & fasteners: stainless steel, motor spring: carbon steel |
| Carabiner | #354-4, 1" opening plated alloy steel, 3,600 lb. gate, min tensile strength 5,000 lbs |
| Snaphook | #RL-28, 3/4" opening alloy steel swivel snap hook, impact indicator |
| | 3,600 lb gate, min tensile strength 5,000 lbs |
| | |

PERFORMANCE SPECIFICATIONS

| | |
|----------------------------|--|
| ANSI User Capacity | 130-310 lbs. Max |
| OSHA User Capacity | 400 lbs. Max |
| Arresting Force | Average arresting force 1,350 lbs, Max 1,800 lbs |
| Max Arrest Distance | 42 inches, max free fall distance 24 inches |

RELEVANT STANDARDS

| | |
|-------------|---------------------------------|
| ANSI | ANSI Z359.14-2021 "Class 2" SRL |
| OSHA | 1926.502 & 1910.66 |
| | |
| | |

SIZES/LENGTHS

30' length
Item weight 6 lbs

