



PRODUCT SPECIFICATIONS

XR-30T Self Retracting Lifeline

Product Description:

The Outlaw Series SRL's provide durability and confidence expected by professionals. With multiple lengths of working capacity and short fall arrest capability, the Outlaw will never let you down.

Product Features:

- 30' Technora® synthetic rope SRL
- Class "1" SRL
- 3/4" opening swivel snaphook
- 1" opening steel carabiner
- Also available in stainless steel or galvanized cable

MATERIAL SPECIFICATIONS

Lifeline Constituent	30' Technora® synthetic rope 3/16", tensile strength 5,600 lbs
Housing/Hardware	Thermo-plastic and aluminum
	Drum: aluminum alloy, main shaft: stainless steel
	Ratchet center & brake pawls: brass
	Springs & fasteners: stainless steel, motor spring: carbon steel
Carabiner	#354-4, 1" opening plated alloy steel 3,600 lb. gate, Min tensile strength 5,000 lbs
Snaphook	#RL-28, 3/4" opening alloy steel swivel snap hook, impact indicator
	3,600 lb gate, Min tensile strength 5,000 lbs

PERFORMANCE SPECIFICATIONS

ANSI User Capacity	130-310 lbs. Max
OSHA User Capacity	400 lbs. Max
Arresting Force	Average arresting force 1,350 lbs, Max 1,800 lbs
Max Arrest Distance	42 inches

RELEVANT STANDARDS

ANSI	ANSI Z359.14-2021 "Class 1" SRL
OSHA	1926.502 & 1910.66

SIZES/LENGTHS

30' length
Item weight 6 lbs

