



PRODUCT SPECIFICATIONS

XR-50LEG Outlaw Leading Edge Self-Retracting Lifeline

Product Description:

The Outlaw Series SRL's provide durability and confidence expected by professionals. All units feature lightweight housings, and short fall arrest capabilities. Leading edge models feature an energy absorption pack to reduce fall arrest forces.

Product Features:

- 50' steel cable
- Class "2" SRL
- 3/4" opening swivel snaphook
- 1" opening steel carabiner
- Energy absorption pack



MATERIAL SPECIFICATIONS

Lifeline	50' galvanized steel cable
Housing/ Hardware	Thermo-plastic and aluminum
	Drum: Aluminum Alloy, Main Shaft: Stainless Steel
	Ratchet Center & Brake Pawls: Brass
	Springs & Fasteners: Stainless Steel, Motor Spring: Carbon Steel
Energy Absorber	Polyester, 1-3/4" tear away
Carabiner	#354-4, 1" Gate Opening Plated Alloy Steel, 3,600 lb. gate, Min tensile strength 5,000 lbs.
Snaphook	3/4" Gate Opening Aluminum Swivel snap with Impact Indicator
	3,600 lb. gate, Min tensile Strength 5,000 lbs

MATERIAL SPECIFICATIONS

Arresting Force	Average arresting force 1,350 lbs., Maximum arresting force 1,800 lbs.
Maximum Arrest distance	42 inches
OSHA Capacity	400 lbs.
ANSI Capacity	130-310 lbs.

RELEVANT STANDARDS

ANSI	ANSI Z359.14-2021 "Class 2" SRL
OSHA	Meets OSHA requirements

SIZES/LENGTHS

50' length
Weight: 10 lbs