



PRODUCT SPECIFICATIONS

22420AS Shock Absorbing Lanyard

Product Description:

A dual-leg, tubular-elastic web lanyard with an internal shock absorbing core. When tested to OSHA and ANSI standards, fall arrest forces are limited up to 900lbs.

Product Features:

- 1-15/16" tubular polyester webbing
- Stretches to minimize tripping and snagging hazards
- Standard 6' length relaxes to 4.5' when not stretched
- Additional snap-hooks available



MATERIAL SPECIFICATIONS

Hardware	#Z74 snap hooks 3/4" gate opening, zinc plated alloy steel
	100% proof loaded to 3,600 lbs, min. tensile 5,000 lbs
Webbing	1-15/16" polyester tubular webbing, min tensile strength 6,000 lbs
Thread	Polyester nubond

PERFORMANCE SPECIFICATIONS

ANSI User Capacity	130-310 lbs. Max
OSHA User Capacity	310 lbs. Max
Arrest Force	900 lbs.
Lanyard Class	6' free fall

RELEVANT STANDARDS

ANSI	ANSI Z359.1-2007
OSHA	Meets or exceeds all OSHA requirements

SIZES/LENGTHS

Standard length 6 Ft, additional lengths available
Item weight 3.8 Lbs