



PRODUCT SPECIFICATIONS

22424AS Shock Absorbing Lanyard

Product Description:

This Dual-Leg Tubular-Elastic Web Lanyard with internal shock absorbing core limits fall arrest forces to 900 lbs. when tested to OSHA and ANSI standards.

Product Features:

- 1-15/16" tubular polyester webbing
- Stretches to minimize tripping and snagging hazards
- Standard length of 6'
- Length of approximately 4.5' when relaxed
- Additional snap-hooks available



MATERIAL SPECIFICATIONS

Hardware	Z74 snap hook, 3/4" gate opening, zinc plated alloy steel
	100% proof loaded to 3,600 lbs min. tensile 5,000 lbs
	100% gate loaded to 3,600 lbs
	Z136 Snap-hooks, 2-1/2" gate opening. zinc plated alloy steel
	100% proof loaded to 3,600 lbs, min. tensile 5,000 lbs
	100% gate loaded to 3,600 lbs
Webbing	1-15/16" black polyester tubular webbing, min tensile strength 6,000 lbs
Thread	White polyester nubond

PERFORMANCE SPECIFICATIONS

ANSI User Capacity	130-310 lbs.
OSHA User Capacity	310 lbs.
Arrest Force	900 lbs
Lanyard Class	6' Free Fall

RELEVANT STANDARDS

ANSI	ANSI Z359.1.2007
OSHA	Meets or exceeds all OSHA requirements

SIZES/LENGTHS

Standard length 6' additional sizes may be available
Item weight 5.0 Lbs.