



PRODUCT SPECIFICATIONS

22444ASZ Shock Absorbing Web Lanyard

Product Description:

Designed to be easy to use, FrenchCreek lanyards feature many styles, options and lengths. This dual leg web lanyard with pack style shock absorber limits fall arrest forces to 900 lbs when tested to OSHA and ANSI standards.

Product Features:

- 1-3/16" polyester webbing with shock pack
- Stretches to minimize tripping and snagging hazards
- Standard length 6', additional lengths available
- Standard 6' length relaxes to 4.5' when not stretched
- Additional snap hook options available



MATERIAL SPECIFICATIONS

Webbing	1 -3/16" polyester tubular webbing, min tensile strength 6,000 lbs
	1-3-4" polyester min tensile strength 6,000 lbs
	Tear away 1-3/4"
Hardware	Z136 snap hooks, 2-1/2" gate opening, zinc plated alloy steel
	100% proof loaded to 3,600 lbs, minimum tensile 5,000 lbs,
	100% gate loaded to 3,600 lbs
	Z74 snap hook, 3/4" gate opening, zinc plated alloy steel
	100% proof loaded to 3,600 lbs, minimum tensile 5,000 lbs,
Thread	gate loaded to 3,600 lbs.
	Polyester nubond

PERFORMANCE SPECIFICATIONS

OSHA User Capacity	130-310 lbs.
ANSI User Capacity	400 lbs.
Arrest Force	900 lbs.
Lanyard Class	6' free fall

RELEVANT STANDARDS

ANSI	Z359.13-2013
OSHA	Meets or exceeds all OSHA requirements

SIZES/LENGTHS

Length 6 ft
Item weight 6.05 lbs