



PRODUCT SPECIFICATIONS

22444AZ Shock Absorbing Web Lanyard

Product Description:

This Dual-Leg Web Lanyard with pack style shock absorber limits fall arrest forces to 900 lbs. when tested to OSHA and ANSI standards.

Product Features:

- 1" nylon webbing with shock pack
- Standard length 6', additional lengths available
- Additional snap-hooks available



MATERIAL SPECIFICATIONS

Hardware	Z74 snap hook, 3/4" gate opening, zinc plated alloy steel
	100% proof loaded to 3,600 lbs min. tensile 5,000 lbs
	100% gate loaded to 3,600 lbs
	Z136 Snap-hooks, 2-1/2" gate opening. zinc plated alloy steel
	100% proof loaded to 3,600 lbs, min. tensile 5,000 lbs
Webbing	1" black nylon, minimum tensile strength 6,000 lbs
	1-3/4" black polyester, minimum tensile strength 6,000 lbs
	Tear away 1-3/4"
Thread	Polyester nubond

PERFORMANCE SPECIFICATIONS

ANSI User Capacity	130-310 lbs.
OSHA User Capacity	400 lbs.
Arrest Force	900 lbs
Lanyard Class	6' Free Fall

RELEVANT STANDARDS

ANSI	ANSI Z359.13.2013
OSHA	Meets or exceeds all OSHA requirements

SIZES/LENGTHS

Standard length 6' additional sizes may be available
Item weight 4.5 Lbs.